



COTURI CU RAZĂ LUNGĂ
R = 1,5 D
LA 30°;45°;60°;90°;180°

Diametru nominal	Diametru exterior	Grosime	Raza	α			C90° C180°	Greut. kg.
				30°	45°	60°		
Dn	De	S	Rc	A			H	
mm	mm	mm	mm	mm	mm	mm	mm	
20	25	2;2,5;3	38	-	16	22	40	0,050
	28							
25	30	2;2,5;3	33,5	-	16	22	48,5	0,100
	32	2;2,5;3	35	-	16	22	51	0,120
	34	2,5;3;3,5	38	-	16	22	55	0,140
32	38	2,5;3;3,5	45	-	20	28	64	0,180
	42	2,5;3;3,5	48	-	20	28	68,5	0,250
40	45	2,5;3;3,5	57	-	24	33	73,5	0,320
	48	2,5;3;3,5 4;4,5	57	-	24	33	81	0,390
50	57	3;3,5;4; 4,5;5;5,5	76	20	31	44	100,5	0,590
	60	3;3,5;4; 4,5;5;5,5	76	20	31	44	106	0,800
65	73	3;3,5;4; 3 ÷ 7	95	25	39	55	128,5	1,690
	76	3 ÷ 7	95	25	39	55	132	1,760
80	89	3 ÷ 7	114	31	47	66	159	2,530
100	102	3,5 ÷ 7	152	41	63	88	184,5	3,410
	108	3,5 ÷ 9	152	41	63	88	196,5	3,870
	114	3,5 ÷ 9	152	41	63	88	209,5	4,390
125	127	8	190	51	79	110	238,5	5,540
	133	4,5 ÷ 9	190	51	79	110	247,5	6,140
	140	4 ÷ 9	190	51	79	110	260,5	8,640
150	159	4 ÷ 11	229	61	95	132	295,5	11,210
	168	5 ÷ 14	229	61	95	132	312	12,570
200	219	6 ÷ 15	305	82	126	176	414,5	22,170
250	273	6 ÷ 18	381	102	158	220	517,5	34,810
300	324	6 ÷ 21	457	122	189	264	619	60,500
350	356	8 ÷ 14	533	143	221	308	711	64,070
400	406	8 ÷ 16	610	163	253	352	812	101,830
450	457	8 ÷ 14	686	-	-	-	914,5	163,90