



COTURI CU RAZĂ SCURTĂ
R = D
LA 30°;45°;60°;90°;180°

Diametru nominal	Diametru exterior	Grosime	Raza	α			C90° C180°	Greut. kg.
				30°	45°	60°		
Dn	De	S	Rc	A			H	
mm	mm	mm	mm	mm	mm	mm	mm	
25	34	3,5	25	-	-	-	42	0,112
32	38	3,5	32	-	-	18	51	0,175
	42	3,5	32	-	-	18	53	0,241
40	48	3,5	38	-	-	22	62	0,272
50	60	4	51	-	21	29	81	0,465
	60	5,5	51	-	21	29	81	0,672
65	73	5	64	-	26	37	100,5	0,633
	76	5	64	-	26	37	102	0,885
80	89	3	76	20	31	44	120,5	0,925
	89	5	76	20	31	44	120,5	1,30
100	102	5,5	102	27	42	59	140	2,65
	114	6	102	27	42	59	159	3,52
125	140	9	127	34	53	73	197	4,15
150	168	7	152	41	63	88	236	7,91
	168	14	152	41	63	88	236	9,77
200	219	8	203	54	84	117	313	13,9
	219	15	203	54	84	117	313	17,3
250	273	9	254	68	105	147	391	27,2
	273	18	254	68	105	147	391	32,4
300	324	9	305	82	126	176	467	39,0
	324	21	305	82	126	176	467	46,4
350	356	9	356	95	147	206	533	50,1
	356	14	356	95	147	206	533	59,8
400	406	9	406	109	168	234	610	78,1
450	457	9	457	-	-	-	686	117,9